TECHNICAL NOTE # 1000

Re: POE-S Devices Certificate Validity Term Change Date: December 9, 2021

On some POE-S devices, with Rev. A software, the certificate validity may be set as one (1) year instead of the default ten (10) years.

To restore certificate validity to ten (10) years, perform the following steps:

- 1. Connect to the device with your browser.
- 2. Select the "Settings" tab to open the "Settings" screen. (*Note: The example below is for the PM-POE-S. The same process would apply for any other POE-S device*).

Apps 🗋 New Tab 🕮 PM-POE-S									
ettings Gable A Gable B	Network -	Reports -						About	[→ Lo
PM-POE-S	Tampe	r Alarm A	Alarm B Fa	ault A	Fault B In	put 1	Input 2	Input 3	Inpu
			PM-POE-S	- # 1					
Node Name	PM-	POE-S - # 1							,
Local Time	2019	-12-11 13:10:43 (America/Phoenix)						
Input		1	2		3			4	
Input State (Secure)		○ N.O.		N.O.	۲	N.O.		• N.O.	
		• N.C.		N.C.		N.C.		N.C.	
Line Supervision		On		On		On		On	
Alarm LED: Red = Alarm, Gray = Se	cure								
Supervision LED: Solid Green = Sec	ure Line, Flashing	g Green = Line Fault,	Gray = No Supervision						
Restore Factory Defaults	Reboot	Backup Config	Restore Config	Browse	No file selecte	d			

- 3. Update the "Local Time" by select the pencil icon at the end of the Local Time field (far right on screen) to open the "Confirm" dialog. Select "Confirm" to update the time.
- 4. Select the "Restore Factory Defaults" button to open the Restore Factory Defaults dialog box as shown below. Un-Check the "Keep network settings" box. Select "Confirm" to restore factory defaults. Certificate validity will now be set to ten (10) years.

🖉 PM-POE-S × +				>				
← → C ▲ Not secure 192.168.1.8/#set	tings			야 ☆ 🖯				
Apps 🗋 New Tab 🕮 PM-POE-S								
Settings Cable A Cable B Net	work - Reports -		, I	About 🛛 🔁 Log Ou				
PM-POE-S	Ta	ut 2 Input 3 Input 4						
SOUTHWEST MICROWAVE	Are you sure you want to Res							
	✓ Keep network settings?							
Node Name		Warning: Restore Factory Defaults triggers a software reset of the device. All configurations settings will be lost and your site will no longer be secure. It is suggested to backup your site before continuing.						
Local Time								
Input								
Input State (Secure)		Cor	nfirm Cancel	• N.O.				
	○ N.C.	○ N.C.	○ N.C.	○ N.C.				
Line Supervision	On	On	On	On				
Alarm LED: Red = Alarm, Gray = Secure								
Supervision LED: Solid Green = Secure Line	, Flashing Green = Line Fault, Gray = No S	upervision						
Restore Factory Defaults Rebo	ot Backup Config Restore	Config Browse No	file selected					